



## **A Mixed Cohesive Law Incorporating Interface Roughness Effects under (near) Pure Mode II Cracking**

**Sørensen, Bent F.; Goutianos, Stergios**

*Publication date:*  
2011

[Link back to DTU Orbit](#)

*Citation (APA):*

Sørensen, B. F., & Goutianos, S. (2011). *A Mixed Cohesive Law Incorporating Interface Roughness Effects under (near) Pure Mode II Cracking*. Abstract from 11th International Conference on the Mechanical Behavior of Material, Lake Como, Italy.

---

### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

# **A Mixed Cohesive Law Incorporating Interface Roughness Effects under (near) Pure Mode II Cracking**

**B. F. Sørensen and S. Goutianos**

Materials Research Division, Risø National Laboratory for Sustainable Energy  
Technical University of Denmark, Frederiksborgvej 399, P.O. Box 49  
4000 Roskilde, Denmark

bsqr@risoe.dtu.dk

## **ABSTRACT**

Experimental investigations of adhesive joints and fibre composites have shown that under pure or near Mode II cracking, the fracture process zone induces a displacement normal to the cracking plane. This effect can be attributed to the roughness of the fracture surface under dominating tangential crack face displacements. As the crack faces displace relatively to each other (contact zone), the roughness asperities ride on top of each other and result in an opening (dilatation) in the normal direction. Furthermore, the interaction of the crack surfaces in the contact zone gives rise to compressive normal stresses and frictional shear stresses opposing the crack face displacements. A mixed mode cohesive zone law, derived from a potential function, is developed to describe the above mentioned fracture behaviour under monotonic opening. The cohesive law is implemented in the commercial finite element program Abaqus. The model is validated against experimental results under various mode mixities.